

Shelvings

Configured in line, L or U, shelvings make it possible to optimize the space of storage, in cold rooms. Easily dismantlable, shelves are machine washable for a perfect hygiene.

Shelvings are composed of a structure (ladder and cladding rails) made of anodised Duralinox (class 15) on which are installed Polymer wire grid shelves, resisting to a temperature of -30°C .

The assembly by conical connection allows a fast assembly without tool as well as a great rigidity and solidity.



Technical characteristics

Height : 168,5 cm overall.
Depth : 36 mm or 46 mm on request

Levels length :
65 cm, 77 cm, 89 cm, 95 cm,
107 cm , 119 cm, 131 cm, 149 cm

Admissible loads :
90 kg per level if properly distributed
that is 450 kg maxi between 2 ladders

Angle connecting piece on all the depth without post.
Easy cleaning thanks to the movable wire grid shelves (dishwasher).
Adjustable levels : every 15 cm, no tools required.



Leg adjustment by jack to correct floor horizontality imperfections.



Specific configuration for Easy Bloc cell



Storage under the refrigerating unit to optimize space.



A complete range of shelvings with an admissible load of 120 kg per level is available on request.

Note :

Documentation available on www.dagard.com



Your distributor



Route du stade - 23600 Boussac - France - tél.+33(0)555.82.40.00 - fax. +33(0)555.65.18.54
info@dagard.com - www.dagard.com